

F44

GLOBAL TRUSS F44 TRUSS SYSTEM

Global Truss represents the highest quality and reliability.

The Global Truss F44 is a 4-point truss system. This provides optimum volume and carrying capacity for its construction size and a tube diameter of only 50mm. This system is connected via a special conical connector system, which is joined together to a complete form fit by means of a copper hammer, creating optimal traction.

The Global Truss F44 finds application in trade fairs and shops, as well as in the event industry in general. It is also characterised by a minimum transport volume and the special lightweight design. The conical connectors are of course included in the scope of delivery - special designs and powder coatings can be carried out at short notice.

Global Truss has the largest truss storage worldwide and is permanently able to deliver all systems. Furthermore, Global Truss is the only truss manufacturer with its own coupler and hook range tested by "TÜV" and "DIN".



TECHNICAL DATA

- Pipe diameter main pipe: 50mm
- Wall thickness: 2mm
- Material: ALMgSi F31 / T6082
- Pipe diameter brace: 25mm x 3mm
- Conical connectors included in scope of delivery

PRODUCED ACCORDING TO


EN 1090-1:2009 + A1:2011

EN 1090-3



INCLUSIVE

LOAD TABLE



The weight of the truss is considered in the load table.

Span	Uniform distribution load	Deflection	Center point load		Point load in third-point		Point load in quarter-point		Point load in fifth-point	
			Deflection	kg	Deflection	kg	Deflection	kg	Deflection	kg
m	kg / m	cm	kg	cm	kg	cm	kg	cm	kg	cm
4,00	716,00	0,92	1232,00	0,64	809,00	0,71	611,00	0,75	517,00	0,81
5,00	481,00	1,52	1037,00	1,06	696,00	1,20	540,00	1,30	444,00	1,36
6,00	342,00	2,25	893,00	1,58	609,00	1,83	483,00	2,02	380,00	2,03
7,00	254,00	3,12	782,00	2,22	540,00	2,60	424,00	2,83	332,00	2,83
8,00	195,00	4,12	694,00	2,97	484,00	3,50	372,00	3,75	294,00	3,77
9,00	154,00	5,26	622,00	3,83	437,00	4,54	332,00	4,79	263,00	4,85
10,00	125,00	6,54	562,00	4,81	398,00	5,73	298,00	5,97	238,00	6,06
11,00	102,00	7,95	512,00	5,91	364,00	7,06	270,00	7,28	216,00	7,42
12,00	85,00	9,50	468,00	7,13	335,00	8,53	246,00	8,73	198,00	8,92
13,00	72,00	11,19	430,00	8,47	309,00	10,15	225,00	10,31	182,00	10,56
14,00	61,00	13,02	397,00	9,94	286,00	11,92	207,00	12,03	168,00	12,34
15,00	53,00	14,99	367,00	11,54	266,00	13,84	191,00	13,89	155,00	14,27
16,00	46,00	17,10	341,00	13,27	248,00	15,91	177,00	15,89	144,00	16,35
17,00	40,00	19,35	317,00	15,14	231,00	18,14	165,00	18,03	134,00	18,58
18,00	35,00	21,75	295,00	17,15	216,00	20,53	153,00	20,32	125,00	20,95
19,00	31,00	24,29	275,00	19,30	202,00	23,08	142,00	22,75	116,00	23,48
20,00	27,00	26,98	257,00	21,61	189,00	25,79	133,00	25,33	109,00	26,16

Technical changes and errors reserved